

BLANK PAGE



Indian Standard SPECIFICATION FOR GAS WASHING BOTTLE

UDC 542.231.2:542.745:666.172.7

© Copyright 1987

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

AMENDMENT NO. 1 JULY 2007 TO

IS 11990: 1986 SPECIFICATION FOR GAS WASHING BOTTLES

(Page 4, clause 4.2) — Substitute the following for the existing clause:

'4.2 Material — The gas washing bottles including the head and dip tubes, shall be made from transparent, clear glass conforming to Class HGB 1 of glass, when graded according to the method prescribed in IS 2303 (Part 1/Sec 1): 1994*.'

(Page 4, footnote marked *) — Substitute the following for the existing:

'*Grading glass for alkalinity Part 1 Hydrolytic resistance, Section 1 Hydrolytic resistance of glass grains at 98°C Method of test and classification (first revision)'

(Page 7, clause 5.2.1) — Substitute the following for the existing clause.

'5.2.1 BIS Certification Mark

The gas washing bottle may also be marked with the Standard Mark.

5.2.1.1 The use of the Standard Mark is governed by the provisions of *Bureau of Indian Standards Act*, 1986 and the Rules and Regulations made thereunder. The details of conditions under which the licence for the use of Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.'

(CHD 10)

Indian Standard

SPECIFICATION FOR GAS WASHING BOTTLES

Laboratoryware and Related Apparatus Sectional Committee, CDC 33

Chairman

Representing

DR M. SANKAR DAS

Bhabha Atomic Research Centre, Bombay

Members

SHRI S. V. GULAVANE (Alternate to

Dr M. Sankar Das)

DR G. S. BAJWA

DR N. K. BANERJEE

DR K. S. RAM (Alternate)

SHRI N. G. BAHAK

SHRI R. SACHDEVA (Alternate)

SHRI M. L. BHAMBANI DR B. B. PAL (Alternate)

SHRI S. K. CHARRABORTI

Defence Science Laboratory, Ministry of Defence

(R & D), New Delhi

Indian Agricultural Research Institute (ICAR).

New Delhi

Directorate General of Technical Development.

New Delhi

National Test House, Calcutta

Scale Development Commissioner (Small

Industries), New Delhi

SHRI S. R. MUNDARGI (Alternate) COL M. CHARRABORTY

Directorate General of Armed Forces Medical Services, Ministry of Defence (DGAFMS).

New Delhi

DR A. V. DIVEKAR **Bio-Science Corporation**, Bombay SERI R. K. GADODIA

Swastik Thermometer Co. Delhi

SHEI D. S. GADODIA (Alternate) SHRI VEDA PRAKASH GUPTA

SHRI S. C. KAPILA (Alternate)

DR R. C. KHERA SHRI D. C. KHERA (Alternate)

SHRI MOHINDER NATH

SHRI B. G. MATHUR (Alternate) SHRI P. R. RAO

SHRI U. T. TEMBE (Alternate)

Hicks Thermometers (India) Ltd, Aligarh

Pushpak Enterprises, Bombay

National Physical Laboratory (CSIR), New

Delhi

Borosil Glass Works Ltd. Bombay

(Continued on page 2)

Copyright 1987 BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

Members

Representing

SHRI H. N. RAVI DR F. L. SALDHANA Modern Instruments, Bangalore Haffkine Institute, Bombay

SHRI A. B. CHUNODKAR (Alternate)

SHRI S. K. SEHGAL

Tarson Products Ltd. Calcutta

SHRI J. C. SHANDILYA Top Syringe Manufacturing Co, Bombay

SHRI J. K. WAD (Alternate)
SHRI G. S. SHUKLA

Ministry of Defence (DGI)

SHRI K. K. AGNIHOTRI (Alternate)

DR B. C. SINHA

Central Glass & Ceramic Research Institute (CSIR), Calcutta

SHRI R. SEN (Alternate) SHRI G. P. SRIVASTAVA

India Meteorological Department, New Delhi

SHRI S. GOPI NATH (Alternate) SHRI SATISH CHANDER.

Director General, BIS (Ex-officio Member)

Director (Chem)

Secretary

SHRIM. M. MALHOTRA Deputy Director (Chem), BIS

General Laboratory Glassware Subcommittee, CDC 33:4

Convener

DR B. C. SINHA

Central Glass and Ceramic Research Institute (CSIR), Calcutta

Members

SHRI S. K. GUPTA (Alternate to

Dr B. C. Sinha)

SHRI U. S. BHARGAVA MAJ N. K. GUPTA (Alternate)

SHRI S. V. GULAVANE DR R. C. KHERA

SHRI G. S. SHUKLA SHRI P. K. GUPTA (Alternate)

SHRIS. A. MERCHANT

DR K. M. PANT

SBRI S. K. CHAKRABORTI

Ministry of Defence (DGAFMS), New Delhi

Bhabha Atomic Research Centre, Bombay

Pushpak Enterprises, Bombay Ministry of Defence (DGI)

Scientific Glass Equipment Manufacturers'

Association, Bombay
National Council of Education Research & Training, New Delhi

Development Commissioner (Small Scale Industries), New Delhi

SHRIS. R. MUNDARGI (Alternate) Borosil Glass Works Ltd, Bombay

SHRI P. R. RAO

SHRI A. K. BANSAL (Alternate) SHRI S. VAIDYANATHAN

Vensil Glass Works Pvt Ltd, Bangalore

Indian Standard SPECIFICATION FOR GAS WASHING BOTTLES

0. FOREWORD

- **0.1** This Indian Standard was adopted by the Indian Standards Institution on 15 December 1986, after the draft finalized by the Laboratoryware and Related Apparatus Sectional Committee had been approved by the Chemical Division Council.
- **0.2** This Indian Standard was prepared with the aim of reducing unnecessary variety in the types and sizes of gas washing bottles used in laboratories. In this standard the Drechsel bottle with fixed head has been prescribed. The dip tube of the bottle may be plain or sintered distributor.
- 0.3 In the formulation of this standard, considerable assistance has been derived from BS: 2461-1983 'Specification for gas washing bottles', issued by the British Standards Institution.
- **0.4** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calulated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes the requirements, and methods of sampling and test for gas washing bottles suitable for general use in laboratories.

2. TERMINOLOGY

2.0 For the purpose of this standard, the following definition in addition to those given in IS: 1382-1981[†], shall apply.

^{*}Rules for rounding off numerical values (revised)
†Glossary of terms relating to glass and glassware (first revision)

2.1 Drechsel Bottle with Fixed Head -- Drechsel bottle as shown in Fig. 1 with standard ground joint at the neck and with dip tube having fixed position.

3. NOMINAL CAPACITIES


3.1 The gas washing bottles shall be of nominal capacities of 125, 250 and 500 ml.

4. REQUIREMENTS

- **4.1 Shape** The shape of gas washing bottles shall be as illustrated in Fig. 1.
- 4.2 Material The gas washing bottles including the head and dip tubes, shall be made from transparent, clear glass conforming to Type 1, when graded according to the method prescribed in IS: 2303-1963*.
- 4.3 Workmanship The gas washing bottles shall be regular in shape with smooth finish and well annealed. These shall be symmetrical about the axis. It shall be reasonably free from visible defects.
- **4.3.1** The gas washing bottles shall be provided with a stable base such that a bottle, complete with head, shall not topple when placed on a surface inclined at 15° to the horizontal, and shall stand firmly and upright on a level surface.
- **4.3.2** Base/Foot The base/foot of the gas washing bottle may be solid, hollow or splay as illustrated in Fig. 2A to Fig. 2C, or as agreed to between the purchaser and the supplier.
- **4.3.3** Ground Glass Joints The ground glass joints of gas washing bottles shall be of sizes 29/32 or 40/38 and shall comply with the requirements of IS: 5156-1969†.
- 4.3.4 Dip Tube The dip tube of gas washing bottle shall be either plain or fitted with sintered distributor as agreed to between the purchaser and the supplier. Sintered distributors, when fitted, shall be of porosity grade number from P 1.6 to P 250 and shall conform to the requirements specified in relevant Indian Standard Specification for laboratory sintered (fritted) filters porosity grading, classification and designation (under preparation).

^{*}Methods of grading glass for alkalinity.

[†]Specification for interchangeable conical ground glass joints.



5

- 4.3.5 The lower tip of the head shall be provided with not less than three supports (for example, indentations) to support the dip tube (see Fig. 1). The outer surface of the head shall be provided with opposing flat surfaces to facilitate grip for safe removal.
- 4.3.6 The gas washing bottles shall be of robust construction to satisfy the requirements of normal use.
- 4.4 Dimensions The gas washing bottles shall comply with the dimensions given in Table 1 and Fig. 1.
- **4.4.1** Tolerance It shall be ± 5 percent on all dimensions when the tolerance is not specified in Table 1 and Fig. 1.

TABLE 1 DIMENSIONS OF GAS WASHING BOTTLES

All dimensions in millimetres,					
DIMENSIONS	Non	NOMINAL CAPACITIES			
	125 ml	250 ml	500		

DIMENSIONS	NOMINAL CAPACITIES		
	125 ml	250 ml	500 ml
(2)	(3)	(4)	(5)
Overall length of the body, l_b	148	188	240
Length from top of the cone to bottom of distributor tube, l_t	130	165	215
External diameter of body, $d_{\rm b}$	48	5 6	70
	(2) Overall length of the body, l_b Length from top of the cone to bottom of distributor tube, l_t	(2) (3) Overall length of the body, l_b 148 Length from top of the cone to bottom of distributor tube, l_t	(2) (3) (4) Overall length of the body, l_b 148 188 Length from top of the cone to bottom of distributor tube, l_t

5. PACKING AND MARKING

- 5.1 Packing The gas washing bottles shall be packed as agreed to between the purchaser and the supplier
- 5.2 Marking The gas washing bottles shall be marked permanently and legibly on its outer surface with the following:
 - a) Name of the manufacturer or his recognized trade-mark, if any;
 - b) Nominal capacity in ml;
 - c) A rough surface or suitably painted one centimetre square for marking purpose;
 - d) Standard joint size on the body and the head part; and
 - e) Porosity grade number on the head, if porous distributor provided.

5.2.1 The gas washing bottle may also be marked with the Standard Mark.

NOTE—The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard Marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers, may be obtained from the Bureau of Indian Standards.

6. SAMPLING

6.1 Representative samples of the gas washing bottle shall be drawn as prescribed in Appendix A.

APPENDIX A

(*Clause* 6.1)

SAMPLING OF GAS WASHING BOTTLES

A-1. SCALE OF SAMPLING

A-1.1 All the gas washing bottles of same type and same capacity in one consignment shall constitute a lot.

A-1.1.1 Samples shall be taken from each lot for ascertaining the conformity to this specification and shall be according to Table 2.

TABLE 2 NUMBER	OF GAS BOTTLES TO	BE SELECTED
Lot Size	Sample Size	Acceptance Number
(1)	(2)	(3)
Up to 50	3	0
51 to 100	5	0
101 to 150	8	1
151 to 300	13	2
301 and above	20	3

A-1.2 The sample shall be selected from the lot at random and in order to ensure randomness of selection, the method given in IS: 4905-1968* may be followed.

A-2. NUMBER OF TESTS AND CRITERIA FOR CONFORMITY

A-2.1 Tests for all the requirements given in 4, except quality of glass (4.2) shall be conducted on each of the bottle selected according to col 2 of Table 2. If a gas bottle fails to meet any of these requirements, it shall be declared as defective and the number of defective bottles in the sample shall not be more than the corresponding acceptance numbers given in col 3 of Table 2.

A-2.2 Test for a quality of glass shall be conducted on two gas bottles and the lot shall be declared as conforming to the requirements of quality of glass if there is no failure in the sample.

^{*}Methods for random sampling.

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW	DELHI 110002	
Telephones: 331 01 31, 331 13 75 Telegrams: Manakeans: (Common to all Office		
Regional Offices:		Telephone
*Western : Manakalaya, E9 MIDC, Marol, Andheri (Eas BOMBAY 400093	1),	6 32 92 95
†Eastern: 1/14 C.I.T. Scheme VII M, V.I.P. Road, Man CALCUTTA 700054	iktola,	36 24 99
Northern: SCO 445-446, Sector 35-C,		[2 18 43
CHANDIGARH 160036		3 16 41
Southern : C.I.T. Campus, MADRAS 600113		{ 41 24 42 41 25 19 41 29 16
Branch Offices:		
'Pushpak', Nurmohamed Shalkh Marg, Khanpur, AHMA	DABAD 380001	2 63 48 2 63 49
'F' Block, Unity Bidg, Narasimharaja Square, BANGAL	ORE 560009	22 48 05
Gangotri Complex, 5th Floor, Bhadbhada Road, T.T. N BHOPAL 462003		6 67 16
Plot No. 82/83, Lewis Road, BHUBANESHWAR 751002	!	5 86 27
53/5, Ward No. 29, R. G. Barua Road, 5th Byelane, GU		
5-8-56C L. N. Gupta Marg (Nampally Station Road), HY		23 10 83
R14 Yudhister Marg, C Scheme, JAIPUR 302005		6 34 71 6 98 32
117/418 B Sarvodaya Nagar, KANPUR 208005		{ 21 68 76 21 82 92
Patiliputra Industrial Estate, PATNA 800013		6 28 05
Hantex Bldg (2nd Floor), Rly Station Road, TRIVANDR	UM 695001	7 66 37
Inspection Offices (With Sale Point):		
Pushpanjali 205-A West High Court Road, Bharampeth NAGPUR 440010	Extension,	2 51 71
Institution of Engineers (India) Building, 1832 Shivaji N	agar, PUNE 411005	5 24 35
*Sales Office in Bombay is at Novelty Chambers, G Bombay 400007	,	89 65 26
†Sales Office in Calcutta is at 5 Chowringhee Appro Princep Street, Calcutta 700072	ech, P.O.	27 68 00